SF19

Fire Rated Multifoil **Insulation**



FIRE RATED INSULATION

CLASS "O" FIRE PROPAGATION & CLASS "1" SPREAD OF FLAME

3 IN 1 DESIGN

FOIL INSULATION, VAPOUR CONTROL & RADIANT BARRIER

EASY TO INSTALL

NO SPECIALIST TOOLS REQUIRED

SUSTAINABLE

MADE FROM UP TO 40% **RECYCLED MATERIALS**

IDEAL FOR USE IN

NEW BUILD & RETROFIT -ROOFS. WALLS & FLOORS





Wall







Fire Rated Multifoil Insulation for Roof, Walls, & Floors.

KEY FEATURES

- SF19FR is from SuperFOIL's fire rated insulation range offering insulation, vapour control, radiant barrier and an additional fire protection.
- The FR products have undergone rigorous testing & have received a British Standard (BS 476) of Class 0 for fire propagation and Class 1 for Spread of flame.
- SuperFOIL can be used on its own, in multiple layers or with any other form of insulation to achieve any U-Value.
- Ideal for use in new build and in retrofit roofs, walls and floors.
- Made from up to 40% recycled materials & is fully recyclable at the end of its lifespan (50+ years).
- Easy to install, with minimal waste.



PRODUCT DIMENSIONS	
Thickness	40mm
Length	10m
Width	1.5m
Coverage	15sqm
Weight	13kg
FIRE PERFORMANCE	
Fire Propagation (BS 476-6)	Class 0
Spread of Flame (BS 476-7)	Class 1
Reaction to Fire (Euroclass)	Class E

Sizes / Figures are approximate & Subject to change without notice, tolerance +/-5%

Boulder Developments Ltd Boulder Business Park Pioneer Way, Lincoln. LN6 OOR, UK Boulder Developments, B.V Ground. 1st. 2nd and 3rd Floor. Joop Geesinkweg 901 999, Amsterdam, 1114 AB, Netherlands

THERMAL PERFORMANCE	
Core	1.31 R Value
Roof (inc. air spaces)	2.27 R Value
Wall (inc. air spaces)	2.73 R Value
Floor (inc. air spaces)	4.37 R Value
Emittance	0.03
ADDITIONAL INFORMATION	
Water vapour resistance	1200MNs/g
Resistance to water penetration	W1
Flexibility at low temperature	-40c
Tensile Properties Length (after ageing)	238/227 N/50mm
Tensile Properties Width (after ageing)	111/100 N/50mm









