PRO GRP HARDENER

Page: 1

Compilation date: 26/08/2016

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PRO GRP HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Hardener for polyester resin

1.3. Details of the supplier of the safety data sheet

Company name: Cromar Building Products Ltd

Units 3, 4 & 5 Northside Industrial Park

Selby Road Whitley Bridge North Yorkshire DN14 0GH

United Kingdom

Tel: 01977663133 **Fax:** 01977662186

Email: sales@cromar.uk.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1B: H314; Acute Tox. 4: H302; Acute Tox. 4: H332; Eye Dam. 1: H318; Org.

Perox. CD: H242

Most important adverse effects: Heating may cause a fire. Harmful if swallowed. Harmful if inhaled. Causes severe skin

burns and eye damage. Causes serious eye damage.

2.2. Label elements

Label elements:

Hazard statements: H242: Heating may cause a fire.

H302: Harmful if swallowed. H332: Harmful if inhaled.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

Hazard pictograms: GHS02: Flame

GHS05: Corrosion

GHS07: Exclamation mark







PRO GRP HARDENER

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+312: IF SWALLOWED: Call a if you feel unwell.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

METHYLETHYLKETONEPEROXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent		
215-661-2	1338-23-4	-	Org. Perox. CD: H242; Skin Corr. 1B: H314; Acute Tox. 4: H302; Acute Tox. 4: H332; Eye Dam. 1: H318	30-50%		
HYDROGEN PEROXIDE SOLUTION						

231-765-0	7722-84-1	-	Ox. Liq. 1: H271; Acute Tox. 4: H332;	1-10%
			Acute Tox. 4: H302; Skin Corr. 1A:	
			H314	

2-METHYLPENTANE-2,4-DIOL

203-489-0	107-41-5	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

PRO GRP HARDENER

Page: 3

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

PRO GRP HARDENER

Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Barely perceptible odour

Evaporation rate: Slow

Oxidising: Oxidising (by EC criteria)

Solubility in water: No data available.

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Boiling point/range°C: No data available. Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 80 Vapour pressure: No data available.

Relative density: 1.11-1.13 pH: Not applicable.

VOC g/I: No data available.

9.2. Other information

Other information: Decomposition temperature >= 60 °C, SADT (UN test H.4), SADT possible at

temperatures above approximately 60 °C.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

PRO GRP HARDENER

Page: 5

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
VAPOURS	HMN	LD50	4.32	mg/l
ORAL	HMN	LD50	1478	mg/kg

Hazardous ingredients:

HYDROGEN PEROXIDE SOLUTION...100%

ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	376	mg/kg
SKN	RAT	LD50	4060	mg/kg

2-METHYLPENTANE-2,4-DIOL

IPR	RAT	LDLO	1500	mg/kg
ORL	MUS	LD50	3097	mg/kg
ORL	RAT	LD50	3700	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

[cont...]

PRO GRP HARDENER

Page: 6

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3105

14.2. UN proper shipping name

Shipping name: ORGANIC PEROXIDE, TYPE D, LIQUID

14.3. Transport hazard class(es)

Transport class: 5.2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

PRO GRP HARDENER

Page: 7

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H242: Heating may cause a fire.

H271: May cause fire or explosion; strong oxidiser.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage. H319: Causes serious eye irritation.

H332: Harmful if inhaled.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.