



HAILO S100 PROFILOT

3-section aluminium combination ladder with LOT System for level adjustment.


THE KEY FEATURES

- LOT System: compensates for uneven ground up to 15 cm. Adjusted by pedal
- Versatile to use as a lean-to, extending or trestle ladder.
- 2 attachable full surface-contact feet and 2 large stable claw feet



OTHER PRODUCT ADVANTAGES


- Locking hook with transport locking mechanism
- Length and cross-profiled rungs
- With step adjustment option (9306-507 / 9309-507)
- Non-removable third ladder section (9312-507)
- Max. load capacity 150kg



SPECIFICATIONS

Level of equipment		5
LOT System		✓
Locking hook with transport locking mechanism		✓
Can be used as lean-to ladder or free-standing ladder		✓
Can be used in a free-standing position		✓
Can be used as lean-to ladder		✓
Step adjustment		✓
Number of steps		2 x 9 + 1 x 8
Width/depth required for setting up lean-to ladder		A = 122 cm, B = 151 cm
Width/depth required for setting up extending ladder		A = 122 cm, B = 169 cm
Height of lean-to ladder		562 cm
Height of extending ladder		421 cm



Max. working height		658 cm
Max. working height of trestle ladder		358 cm
Max. working height of lean-to ladder		658 cm
Max. working height of extending ladder		465 cm
Dimensions of packaging (HxWxD)		A = 274 cm, B = 48 cm, C = 19 cm
Step adjustment max.		54 cm
Weight		21,7 kg
Load capacity		150 kg